Sample PBS Script for Pleiades

Category: PBS on Pleiades

DRAFT

This article is being reviewed for completeness and technical accuracy.

```
#PBS -S /bin/csh
#PBS -N cfd
# This example uses the Harpertown nodes
# User job can access ~7.6 GB of memory per Harpertown node.
# A memory intensive job that needs more than ~0.9 GB
# per process should use less than 8 cores per node
# to allow more memory per MPI process. This example
# asks for 64 nodes and 4 MPI processes per node.
# This request implies 64x4 = 256 MPI processes for the job.
#PBS -l select=64:ncpus=8:mpiprocs=4:model=har
#PBS -l walltime=4:00:00
#PBS -i oe
#PBS -W group_list=a0801
#PBS -m e
# Currently, there is no default compiler and MPI library set.
# You should load in the version you want.
# Currently, MVAPICH or SGI's MPT are available in 64-bit only,
# you should use a 64-bit version of the compiler.
module load comp-intel/11.1.046
module load mpi-sqi/mpt.2.04.10789
# By default, PBS executes your job from your home directory.
# However, you can use the environment variable
# PBS_O_WORKDIR to change to the directory where
# you submitted your job.
cd $PBS_O_WORKDIR
# use of dplace to pin processes to processors may improve performance
# Here you request to pin processes to processors 2, 3, 6, 7 of each node.
# This helps for using the Harpertown nodes, but not for Nehalem-EP or
# Westmere-EP nodes
# The resource request of select=64 and mpiprocs=4 implies
# that you want to have 256 MPI processes in total.
# If this is correct, you can omit the -np 256 for mpiexec
# that you might have used before.
mpiexec dplace -s1 -c2,3,6,7 ./grinder < run_input > output
```

```
# It is a good practice to write stderr and stdout to a file (ex: output)
```

-end of script-

Article ID: 190

Last updated: 03 Oct, 2011

Computing at NAS -> Running Jobs with PBS -> PBS on Pleiades -> Sample PBS Script

for Pleiades

http://www.nas.nasa.gov/hecc/support/kb/entry/190/?ajax=1

Category: PBS on Pleiades

[#] Otherwise, they will be written to the PBS stderr and stdout in /PBS/spool,

[#] which has limited amount of space. When /PBS/spool is filled up, any job

[#] that tries to write to /PBS/spool will die.